

Sunsui's **Wireless Temperature Humidity transmitter** is best suitable and economical solution for applications where the sensor wiring is not possible. This sensor will be used for monitoring the temperature and humidity. The unit is wall mountable and portable. Compact size makes it easy to relocate in case user wants to change the position of the sensor.



Model: WiFi-RHT-LED

TT-HH Transmitter with 7
Segment Display



Model: WiFi-RHT-LCD

TT-HH Transmitter with LCD
TFT Display

Technical Specifications

Description	Details
Range:	Temperature: -40°C to +60°C Humidity: 0% to 100% RH
Accuracy :	Temperature: +/- 0.5°C Humidity: +/- 3% RH
Resolution:	Temperature: 0.1°C Humidity: 0.1% RH
Wireless Frequency:	868 MHz License Free Band
Display:	1) 4Digit-7 segment RED and Green LED display. 2) LCD TFT display
Transmission Frequency:	Every 1 Minute / 3Min / 5Min / 15Min Selectable
Power Supply:	12VDC adapter.
Housing Material:	ABS Plastic

Sunsui Process System, India

(ISO 9001:2015 Certified Company)

Ashwamedh Commercia, 1st Floor, Mumbai-Bangalore Highway, Baner, Pune 411045, Maharashtra, India



+91 95455 21323 / +91 9284136565



sales@sunsuiprocess.com / sunsuiprocess@gmail.com



www.sunsuiprocess.com / www.dataloggersindia.in

(Dealer Stamp)